


Up to 25 l/min
Up to 350 bar

FUNCTION



When the solenoid coil is de-energized, all ports are closed.

When the solenoid coil is energized, there is free flow through the valve from port 3 to 2 or from 2 to 3 and also from port 4 to 1 or from 1 to 4.

4/2 Solenoid Directional Valve Spool Type, Direct-Acting, Metric Cartridge – 350 bar WKM08140EB-01

FEATURES

- Coil seals protect the solenoid system
- Wide variety of connectors available
- Hardened and ground control spool to ensure minimal wear and extended service life
- Low pressure drop due to CFD optimized flow path
- External surfaces zinc-plated and corrosion-proof
- Excellent stability throughout the entire flow range
- Compact design enables space-saving installation in connection housings and control blocks


SPECIFICATIONS

Operating pressure:	max. 350 bar
Nominal flow:	max. 25 l/min
Internal leakage:	max. 150 cm ³ /min at 250 bar and 34 mm ² /s
Media operating temperature range:	min. -20 °C to max. +100 °C
Ambient temperature range:	min. -20 °C to max. +60 °C
Operating fluid:	Hydraulic oil to DIN 51524 Part 1 and 2
Viscosity range:	min. 10 mm ² /s to max. 420 mm ² /s
Filtration:	Class 21/19/16 according to ISO 4406 or cleaner
MTTF _d :	150 years (see "Conditions and instructions for valves" in brochure 5.300)
Installation:	No orientation restrictions
Materials:	Valve body: free-cutting steel Spool: hardened and ground steel Seals: NBR (standard) FKM (optional, media temperature range -20 °C to 120 °C) Back-up rings: PTFE Coil: steel / polyamide
Cavity:	08140
Weight:	Valve complete 0.38 kg Coil only 0.19 kg


Electrical data:

Type of voltage:	DC solenoid, AC voltage is rectified using a bridge rectifier built into the coil
Current draw at 20 °C:	1.5 A at 12 V DC 0.8 A at 24 V DC
Voltage tolerance:	± 15% of the nominal voltage
Coil duty rating:	Continuous up to max. 115% of the nominal voltage at 50 °C ambient temperature
Response time:	Energized: approx. 40 ms De-energized: approx. 30 ms
Coil type:	Coil...-40-1836

After loosening the mounting nut, the coil can be rotated through 360° and removed.

 $\nu = 34 \text{ mm}^2/\text{s}, T_{\text{oil}} = 46 \text{ }^\circ\text{C}$ 

08140



Tool	Part No.
Countersink (shank HE25)	163463
Reamer (shank MK2)	163464

millimeter
subject to technical modifications

WKM08140EB - 01 M - C - N - 24 DG

Other connectors on request


Model code	Part No.
WKM08140EB-01-C-N-24DG	3117855
WKM08140EB-01-C-N-230AG	3117854

Code	Part No.	Material	Ports	Pressure
R08140-01X-01	394473	Steel, zinc-plated	G 3/8	420 bar
R08130-01X-02	393535	Steel, zinc-plated	M 14 x 1.5	420 bar

Other bodies on request

Code	Material	Part No.
SEAL KIT 08130-NBR	NBR	3164596
SEAL KIT 08130-FKM	FKM	3183746

Measured at $\nu = 33 \text{ mm}^2/\text{s}$, $T_{\text{oil}} = 46 \text{ }^\circ\text{C}$



NOTE
The information in this brochure relates to the operating conditions and applications described. For applications or operating conditions not described, please contact the relevant technical department.
Subject to technical modifications.

HYDAC Fluidtechnik GmbH
Justus-von-Liebig-Str.
D-66280 Sulzbach/Saar
Tel: 0 68 97 /509-01
Fax: 0 68 97 /509-598
E-Mail: flutec@hvdac.com